

SMART METER

SINGLE PHASE/THREE PHASE



Simple & Easy

LCD display, easy to set and check



Energy Efficient

Overall power consumption ≤ 1 W



Accurate

Class 1 measurement accuracy

Technical Specification	DDSU666	DTSU666	DTSU666 100A/40mA
General Data			
Dimension (H x W x D)	100 x 36 x 65.5 mm (3.9 x 1.4 x 2.6 inch)	100 x 72 x 65.5 mm (3.9 x 2.8 x 2.6 inch)	
Mounting type		DIN35 Rail	
Weight (including cables)	1.2 kg (2.6 lb)	1.5 kg (3.3 lb)	
Power Supply			
Power grid type	1P2W	3P4W/3P3W	
Input voltage (phase voltage)		176 Vac ~ 288 Vac	
Power consumption	≤ 0.8 W	≤ 1 W	
Measurement Range			
Line voltage	/	304 Vac~ 499 Vac	
Phase voltage		176 Vac ~ 288 Vac	
Current	0 ~ 100 A	0 ~ 250 A	
Measurement Accuracy			
Voltage		± 0.5 %	
Current / Power / Energy		± 1 %	
Frequency		± 0.01 Hz	
Communication			
Interface		RS485	
Baud rate		9,600 bps	
Communication protocol		Modbus-RTU	
Environment			
Operating temperature range		-25~60 °C	
Storage temperature range		-40~70 °C	
Operating humidity		5 %RH ~ 95 %RH (non-condensing)	
Others			
Accessories	RS485 Cable (10 m / 33 ft.)		3 CT 100A / 40mA (5m / 16.4 ft.) 